

# Xiamen Linkup Magnet Co.,Ltd

## Magnetic Properties Of Ferrite Magnet



Grade	Remanence Br		Coercivity Hcb		Intrinsic Coercivity Hcj		Maximum Energy Product (BH)max	
	mT	Gs	kA/m	Oe	kA/m	Oe	kJ/m <sup>3</sup>	MGOe
Y8T	200-235	2000-2350	125-160	1570-2010	210-280	2640-3520	6.5-9.5	0.82-1.19
Y25	360-400	3600-4000	135-170	1700-2140	140-200	1760-2520	22.5-28.0	2.83-3.52
Y26H-1	360-390	3600-3900	200-250	2520-3140	225-255	2830-3200	23.0-28.0	2.89-3.52
Y28	370-400	3700-4000	175-210	2200-2640	180-220	2260-2760	26.0-30.0	3.27-3.77
Y28H-1	380-400	3800-4000	240-260	3015-3270	250-280	3140-3520	27.0-30.0	3.39-3.77
Y28H-2	360-380	3600-3800	271-295	3405-3705	382-405	4800-5090	26.0-28.5	3.27-3.58
Y30H-1	380-400	3800-4000	230-275	2890-3450	235-290	2950-3650	27.0-31.5	3.39-3.96
Y30H-2	395-415	3950-4150	275-300	3450-3770	310-335	3900-4210	27.0-32.0	3.39-4.02
Y32	400-420	4000-4200	160-190	2010-2400	165-195	2080-2450	30.0-33.5	3.77-4.21
Y32H-1	400-420	4000-4200	190-230	2400-2900	230-250	2900-3140	31.5-35.0	3.96-4.40
Y32H-2	400-440	4000-4400	224-240	2800-3020	230-250	2900-3140	31.0-34.0	3.89-4.27
Y33	410-430	4100-4300	220-250	2760-3140	225-255	2830-3200	31.5-35.0	3.96-4.40
Y33H	410-430	4100-4300	250-270	3140-3400	250-275	3140-3450	31.5-35.0	3.96-4.40
Y33H-2	410-430	4100-4300	285-315	3580-3960	305-335	3830-4210	31.8-35.0	4.0-4.40
Y34	420-440	4200-4400	250-280	3140-3520	260-290	3270-3650	32.5-36.0	4.08-4.52
Y35	430-450	4300-4500	230-260	2900-3270	240-270	3015-3400	33.1-38.2	4.16-4.80
Y36	430-450	4300-4500	260-290	3270-3650	265-295	3330-3705	35.1-38.3	4.41-4.81
Y38	440-460	4400-4600	285-315	3580-3960	295-325	3705-4090	36.6-40.6	4.60-5.10
Y40	440-460	4400-4600	315-345	3960-4340	320-350	4020-4400	37.6-41.6	4.72-5.23
Y41	450-470	4500-4700	245-275	3080-3460	255-285	3200-3580	38.0-42.0	4.77-5.28
Y41H	450-470	4500-4700	315-345	3960-4340	385-415	4850-5220	38.5-42.5	4.84-5.34
Y42	460-480	4600-4800	315-335	3960-4210	355-385	4460-4850	40.0-44.0	5.03-5.53
Y42H	460-480	4600-4800	325-345	4080-4340	400-440	5020-5530	40.0-44.0	5.03-5.53
Y43	465-485	4650-4850	330-350	4150-4400	350-390	4400-4900	40.5-45.5	5.09-5.72

Welcome to contact us for further informations.

Sales@linkupmagnets.com